

TECHNICAL SPECIFICATIONS

KC9

WORKING TEMPERATURE

Depends on the tube used

RANGE DIAMETER TUBES

From Ø8 to Ø90

REFERENCE STANDARD

Reach - RoHS2

CONSTRUCTION MATERIALS

Housing & band: stainless steel AISI 430

Screw: zinc plated steel with white trivalent zinc plating

KCW9

WORKING TEMPERATURE

Depends on the tube used

RANGE DIAMETER TUBES

From Ø8 to Ø90

REFERENCE STANDARD

Reach - RoHS2

CONSTRUCTION MATERIALS

Housing, screw & band: stainless steel AISI 304

KCX9

WORKING TEMPERATURE

Depends on the tube used

RANGE DIAMETER TUBES

From Ø8 to Ø90

REFERENCE STANDARD

Reach - RoHS2

CONSTRUCTION MATERIALS

Housing, screw & band: stainless steel AISI 316

5090

WORKING TEMPERATURE

+4°C ÷ +90°

RANGE DIAMETER TUBES

From Ø8 to Ø49

REFERENCE STANDARD

Reach - RoHS2

CONSTRUCTION MATERIALS

Acetal resin

FEATURES

The acetal resin clamps are strong, durable, reusable

