



Temperature depends on the tube used, so their values will be defined according to the features of the tube itself.
 NBR -20°C ÷ +100°C
 VITON -15°C ÷ +200°C



Up to 60 Bar
 Pressure depends on the tube used, so their values will be defined according to the features of the tube itself.



Compressed air, water and fluids suitable with construction materials



Taper gas BSPT ISO 7 from R1/8" to R1"
 Parallel gas BSPP ISO 228 from G1/8" to G3/4"
 Metric M5 and M6



Body: nickel plated brass
 UNI EN 12164 CW 614N and
 UNI EN 12164 CW 617N

Lathed: nickel plated brass
 UNI EN 12164 CW 614N

Printed: nickel plated brass
 UNI EN 12164 CW 617N

O'ring: NBR or Viton

Available on demand and with minimum quantity in yellow brass



Products in compliance with the directive 2002/95/EC

RoHS2

Products in compliance with the directive 2011/65/EU

DIAMETER OF THE BARB

ØD	Ø 4,5 mm	Ø 6 mm	Ø 7 mm	Ø 8 mm	Ø 9 mm	Ø10 mm	Ø 12 mm	Ø 14 mm	Ø 17 mm	Ø 18 mm	Ø 20 mm
ØB (mm)	5,0 mm	6,15 mm	7,15 mm	8,15 mm	9,20 mm	10,20 mm	12,20 mm	14,25 mm	17,30 mm	18,50 mm	20,60 mm

